



Our main goal is to provide the customer with the highest satisfaction if it comes to flexibility of our offer and individual solutions. Pass-through drying ovens are based on standard models of drying ovens and are available in 2 versions: 112, 245 liters. Each request for such equipment is given professional advice and is discussed in details, therefore we kindly ask you to contact us on this matter.



Parameter		Model	SLWP 115	SLWP 240
				
air convection			forced	
chamber capacity <sup>1</sup>	[l]		112	245
	[cu ft]		3,9	8,6
door type			solid / door with viewing window (option)	
temperature range	[°C]		5° above ambient temperature...+300°	
	[°F]		41° above ambient temperature...+572°	
controller			microprocessor with external LCD graphic display	
interior			acid-proof stainless steel according to DIN 1.4301	
housing			powder coated sheet / stainless steel linen finish (INOX/G)	
overall dims* [mm]	width		650	815
	height		885	1180
	depth		630	690
internal dims [mm]	width		460	600
	height		540	800
	depth		480	540
max shelf workload [kg]	-		10	10
	PW version		50	100
max unit workload [kg]	-		60	90
	W version		120	300
nominal power [W]			2400	3000
weight [kg]			65	126
temperature resolution [°C]			every 0,1	
temperature fluctuation <sup>2</sup> at +105°C [°C]			±0,5	±0,5
over temperature protection			class 2.0	
voltage 50 /60 Hz [V]			110-120/220-240	
shelves fitted / max <sup>3</sup>			2/7	3/10
warranty			24 months	
manufacturer			POL-EKO-APARATURA	

\* - dims of door handles, power cable and leveling feet or wheels not included

1 - working capacity of chamber can be smaller

2 - fluctuation measured in centre of the chamber

3 - "fitted" - number of shelves fitted, included in price, "max" - number of shelves which can be fitted